



CHAM'ALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAM'ALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

ТЕХНИЧЕСКА ИНФОРМАЦИЯ

КОНТАКТНО ЛЕПИЛО НА СПРЕЙ

Код: **26803**

Цвят: **белезникаво- транспарентен**

Приложение: **Авторепаратурен продукт/ микс Лепило/ Слепващо вещество**
Основни характеристики: **Многофункционално контактно лепило за дълготрайна или временна адхезия. Скоростта на пръскане може да се контролира чрез регулируем клапан. Безпроблемно, лесно приложение. За употреба върху: килим, корк, гума, порест каучук, хартия, картон, текстил, кожа, метал, дърво, много пластмаси и др.**

Физични и химични свойства:

Основно свързващо вещество: синтетична смола

Мирис: характерен

Производителност: 1,2 g/sec.

Парно налягане при 20°C: 3 - 4 bar

Топлоустойчив: до 80°C

Стабилност при съхранение: 10 години при подходящо съхранение (=10°-25°C, относителна влажност на въздуха макс. 60%)

Размер: аерозолна кутия , максимален номинален обем 400 мл

:

!

-
-
-

: 5° 30°C

,

- - Shake the can for 2 minutes before use.
 - Spray at a distance of ca. 25-30 cm – further for polystyrene foam.
 - Long-lasting adhesion: apply adhesive to both sides. After 15-20 minutes drying time, press the surfaces together.
 - Temporary adhesion: Apply a thin even amount to the material and press them together after 5 -10 minutes.
 - Apply more to extra absorbent materials. Press both pieces of material together till the adhesive dries.
 - After use, turn can upside down and spray empty to clean the valve.

Tips for spray painting:

Protect the object and the surrounding area from spray mist.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Drying		Drying time	Glue time / active time
Object temperature	20 °C, 50% relative air humidity	2 - 5 min.	max. 45 min.

The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.

Environment and labelling

Environmentally compatible: Chamäleon GmbH is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of Chamäleon GmbH comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:
e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.